

SCHOTTKY BARRIER RECTIFIERS

VOLTAGE RANGE: 20 --- 40 V
CURRENT: 3.0 A


FEATURES

- ◇ Metal-Semiconductor junction with guard ring
- ◇ Epitaxial construction
- ◇ Low forward voltage drop, low switching losses
- ◇ High surge capability
- ◇ For use in low voltage, high frequency inverters free wheeling, and polarity protection applications
- ◇ The plastic material carries U/L recognition 94V-0

MECHANICAL DATA

- ◇ Case: JEDEC DO-27, molded plastic
- ◇ Terminals: Axial lead, solderable per MIL-STD-202, method 208
- ◇ Polarity: Color band denotes cathode
- ◇ Weight: 0.041 ounces, 1.15 grams
- ◇ Mounting position: Any

DO - 27



Dimensions in millimeters

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load. For capacitive load, derate by 20%.

		1N5820	1N5821	1N5822	UNITS
Maximum recurrent peak reverse voltage	V_{RRM}	20	30	40	V
Maximum RMS voltage	V_{RMS}	14	21	28	V
Maximum DC blocking voltage	V_{DC}	20	30	40	V
Maximum average forward rectified current 9.5mm lead length, $\text{@ } T_A = 75^\circ\text{C}$	$I_{F(AV)}$		3.0		A
Peak forward surge current 8.3ms single half-sine-wave superimposed on rated load	I_{FSM}		80.0		A
Maximum instantaneous forward voltage @ 3.0A (Note 1) @ 9.4A	V_F	0.475 0.85	0.50 0.90	0.525 0.95	V
Maximum reverse current $\text{@ } T_A = 25^\circ\text{C}$ at rated DC blocking voltage $\text{@ } T_A = 100^\circ\text{C}$	I_R		2.0 20.0		mA
Typical junction capacitance (Note2)	C_J	210		165	pF
Typical thermal resistance (Note3)	$R_{\theta JA}$		20		°C/W
Operating junction temperature range	T_J		- 55 ---- + 125		°C
Storage temperature range	T_{STG}		- 55 ---- + 150		°C

NOTE: 1. Pulse test : 300 μs pulse width, 1% duty cycle.

www.galaxycn.com

2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

3. Thermal resistance junction to ambient

RATINGS AND CHARACTERISTIC CURVES

1N5820 -- 1N5822

AVERAGE FORWARD RECTIFIED CURRENT
AMPERES




FIG.1 – FORWARD DERATING CURVE

PEAK FORWARD SURGE CURRENT
AMPERES




FIG.2 – PEAK FORWARD SURGE CURRENT

INSTANTANEOUS FORWARD CURRENT
AMPERES




FIG.3 – TYPICAL INSTANTANEOUS FORWARD
CHARACTERISTICS

CAPACITANCE, pF




FIG.4 – TYPICAL JUNCTION CAPACITANCE