

Features

- Low turn-on voltage.
- Fast switching.
- Ultra-small surface mount package.
- PN Junction Guard Ring for Transient and ESD Protection.


HF

Typical Applications


- General purpose switching application.

Mechanical Data


- Case: SOT-523
- Terminals: solderable per MIL-STD-202, Method 208.




BAS40T



BAS40-04T



BAS40-05T



BAS40-06T



SOT-523

Ordering Information

Part Number	Package	Shipping	Marking Code
BAS40T	SOT-523	3000 pcs / Tape & Reel	43
BAS40-04T	SOT-523	3000 pcs / Tape & Reel	44
BAS40-05T	SOT-523	3000 pcs / Tape & Reel	45
BAS40-06T	SOT-523	3000 pcs / Tape & Reel	46

Maximum Ratings (@T_A=25°C unless otherwise specified)

Parameter	Symbol	Limits	Unit
Peak Repetitive Peak Reverse Voltage	V _{RRM}	40	V
Working Peak Reverse Voltage	V _{RWM}		
DC Reverse Voltage	V _R		
RMS Reverse Voltage	V _{R(RMS)}	28	V
Forward Continuous Current *	I _{FM}	200	mA
Non-Repetitive Peak Forward Surge Current @8.3ms	I _{FSM}	600	mA
Power Dissipation *	P _d	150	mW

* part mounted on FR-4 board with recommended pad layout

Thermal Characteristics

Parameter	Symbol	Limits	Unit
Thermal Resistance, Junction to Ambient Air	$R_{\theta JA}$	667	$^{\circ}C/W$
Operating Junction Temperature Range	T_j	-55 to +125	$^{\circ}C$
Storage Temperature Range	T_{STG}	-55 to +150	$^{\circ}C$





Electrical Characteristics (@ $T_A=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward Voltage *1	V_F	$I_F=1mA$			0.38	V
		$I_F=40mA$			1	V
Reverse Leakage Current *2	I_R	$V_R=30V$			200	nA
Capacitance Between Terminals	C_T	$V_R=0V, f=1MHz$		2.5	5	pF
Reverse Recovery Time	t_{rr}	$I_F=I_R=10mA$ $I_{rr}=1.0mA, R_L=100\Omega$			5	ns

*1: pulse test, $t_p \leq 300\mu s$


*2: pulse test, $t_p \leq 5ms$

Ratings and Characteristic Curves ($T_A=25^{\circ}C$ unless otherwise noted)



Package Outline Dimensions (unit:mm)


SOT-523



SOT-523		
Dim	Min	Max
A	1.50	1.70
B	0.75	0.85
C	0.60	0.80
D	0.15	0.30
E	0.30	0.40
F	0.25	0.40
G	0.90	1.10
H	0.02	0.10
J	0.08	0.18
K	1.45	1.75

Mounting Pad Layout (unit:mm)

SOT-523



IMPORTANT NOTICE

Galaxy Microelectronics (GME) reserves the right to make changes without further notice to any product herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.