


Features

- Complementary P + N channel
- Advanced trench technology
- Exceptional on-resistance and maximum DC current capability

HF

Mechanical Data

- Case: SOT-23-6L
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208


SOT-23-6L

Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
BL2038D-6L	SOT-23-6L	3000 pcs / Tape & Reel	2038D

Maximum Ratings (@ T_A = 25°C unless otherwise specified)

Parameter	Symbol	Q1	Q2	Unit
Drain-to-Source Voltage	V _{DSS}	20	-20	V
Gate-to-Source Voltage	V _{GSS}	±12	±12	V
Continuous Drain Current (T _A = 25°C) ^{*1}	I _D	3.2	-2.3	A
Continuous Drain Current (T _A = 70°C) ^{*1}		2.6	-1.8	A
Pulsed Drain Current (t _p = 10μs, T _A = 25°C)	I _{DM}	16	-12	A
Single Pulse Avalanche Energy ^{*4}	E _{AS}	2	2	mJ
Power Dissipation (T _A = 25°C) ^{*1}	P _D	1		W
Power Dissipation (T _A = 25°C) ^{*2}		0.5		W
Operating Junction Temperature Range	T _J	-55 ~ +150		°C
Storage Temperature Range	T _{STG}	-55 ~ +150		°C

Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance Junction-to-Air ^{*1}	R _{θJA}	-	100	125	°C/W
Thermal Resistance Junction-to-Air ^{*2}	R _{θJA}	-	-	250	°C/W

Notes:

1. The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper
2. The data tested by surface mounted on a minimum recommended FR-4 board

Electrical Characteristics-Q₁ (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = 250μA	20	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = 20V, V _{GS} = 0V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±12V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DSON}	Drain-Source On-resistance ^{*3}	V _{GS} = 4.5V, I _D = 3A	-	54	65	mΩ
		V _{GS} = 2.5V, I _D = 2A	-	76	85	mΩ
V _{Gsth}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = 250μA	0.5	0.9	1.2	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	17	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = 10V f = 1.0MHz	-	188	-	pF
C _{OSS}	Output Capacitance		-	28	-	
C _{RSS}	Reverse Transfer Capacitance		-	22	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time ^{*5}	V _{DD} = 10V V _{GS} = 4.5V I _D = 1A R _G = 6Ω	-	5	-	ns
t _r	Turn-on Rise Time ^{*5}		-	8.5	-	
t _{d(OFF)}	Turn-Off Delay Time ^{*5}		-	11	-	
t _f	Turn-Off Fall Time ^{*5}		-	3	-	
Q _G	Total Gate-Charge	V _{DD} = 10V V _{GS} = 4.5V I _D = 3.6A	-	3.3	-	nC
Q _{GS}	Gate to Source Charge		-	0.8	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	0.6	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage ^{*3}	I _F = 1A, V _{GS} = 0V	-	0.8	1.2	V

Electrical Characteristics-Q₂ (@ T_A = 25°C unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
Static Characteristics						
V _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0V, I _D = -250μA	-20	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} = -20V, V _{GS} = 0V	-	-	-1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} = ±12V, V _{DS} = 0V	-	-	±100	nA
On Characteristics						
R _{DSON}	Drain-Source On-resistance ^{*3}	V _{GS} = -4.5V, I _D = -1.5A	-	118	140	mΩ
		V _{GS} = -2.5V, I _D = -1.1A	-	157	180	mΩ
V _{Gsth}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _D = -250μA	-0.4	-0.6	-1.0	V
R _G	Gate Resistance	V _{GS} = 0V, f = 1MHz	-	40	-	Ω
Dynamic Characteristics						
C _{ISS}	Input Capacitance	V _{GS} = 0V V _{DS} = -10V f = 1.0MHz	-	199	-	pF
C _{OSS}	Output Capacitance		-	29	-	
C _{RSS}	Reverse Transfer Capacitance		-	22	-	
Switching Characteristics						
t _{d(ON)}	Turn-on Delay Time ^{*5}	V _{DD} = -10V V _{GS} = -4.5V I _D = -1A R _G = 5Ω	-	11	-	ns
t _r	Turn-on Rise Time ^{*5}		-	5	-	
t _{d(OFF)}	Turn-Off Delay Time ^{*5}		-	20	-	
t _f	Turn-Off Fall Time ^{*5}		-	8	-	
Q _G	Total Gate-Charge	V _{DD} = -16V V _{GS} = -4.5V I _D = -1.5A	-	3.5	-	nC
Q _{GS}	Gate to Source Charge		-	0.7	-	
Q _{GD}	Gate to Drain (Miller) Charge		-	0.8	-	
Source-Drain Diode Characteristics						
V _{SD}	Diode Forward Voltage ^{*3}	I _{SD} = -1.5A, V _{GS} = 0V	-	-0.9	-1.1	V

Notes:

3. The data tested by pulsed, pulse width ≤ 300μs, duty cycle ≤ 2%
4. The E_{AS} data shows Max. rating. N: The test condition is V_{DD} = 15V, V_{GS} = 10V, L = 0.1mH;
P: The test condition is V_{DD} = -15V, V_{GS} = -10V, L = 0.1mH
5. Guaranteed by design, not subject to production

Ratings and Characteristics Curves-Q₁ (@ T_A = 25°C unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature




Fig 12 Normalized V_{GS(th)} vs. Junction Temperature

Ratings and Characteristics Curves-Q₂ (@ T_A = 25°C unless otherwise specified)




Fig 1 Power Dissipation




Fig 2 Drain Current




Fig 3 Typical Output Characteristics




Fig 4 On-Resistance vs. Drain Current and Gate Voltage




Fig 5 On-Resistance vs. Gate-Source Voltage




Fig 6 Body-Diode Characteristics




Fig 7 Normalized On-Resistance vs. Junction Temperature




Fig 8 Transfer Characteristics




Fig 9 Capacitance Characteristics




Fig 10 Gate-Charge Characteristics




Fig 11 Normalized Breakdown Voltage vs. Junction Temperature





Fig 12 Normalized V_{GS(th)} vs. Junction Temperature


Package Outline Dimensions (Unit: mm)



SOT-23-6L		
Dimension	Min.	Max.
A	2.80	3.00
B	1.50	1.70
C	1.00	1.20
D	0.35	0.45
E	0.35	0.55
G	0.90	1.00
H	0.02	0.10
J	0.10	0.20
K	2.60	3.00

Package Outline Dimensions (Unit: mm)

SOT-23-6L



IMPORTANT NOTICE

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.