

### Features

- Very low FOM  $R_{DS(on)} \times Q_G$
- 100% Avalanche Tested



HF

### APPLICATIONS

- Switch Mode Power Supply (SMPS)
- Power Factor Correction (PFC)
- Uninterruptible Power Supply (UPS)

### Mechanical Data

- Case: ITO-220AB
- Molding Compound: UL Flammability Classification Rating 94V-0
- Terminals: Matte tin-plated leads; solderability-per MIL-STD-202, Method 208



ITO-220AB

### Ordering Information

Part Number	Package	Shipping Quantity	Marking Code
SJM60R240F	ITO-220AB	50 pcs / Tube	SJM60R240F

### Maximum Ratings (@ $T_J = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Value	Unit
Drain-Source Voltage	$V_{DS}$	600	V
Gate-Source Voltage	$V_{GS}$	$\pm 30$	V
Continuous Drain Current	$I_D$	15	A
Pulsed Drain Current <sup>*1</sup>	$I_{DM}$	45	A
Single Pulse Avalanche Energy <sup>*2</sup>	$E_{AS}$	284	mJ

### Thermal Characteristics

Parameter	Symbol	Value	Unit
Power Dissipation ( $T_C = 25^\circ\text{C}$ )	$P_D$	32	W
Thermal Resistance Junction-to-Air	$R_{\theta JA}$	80	$^\circ\text{C/W}$
Thermal Resistance Junction-to-Case	$R_{\theta JC}$	3.9	$^\circ\text{C/W}$
Operating Junction Temperature Range	$T_J$	-55 ~ +150	$^\circ\text{C}$
Storage Temperature Range	$T_{STG}$	-55 ~ +150	$^\circ\text{C}$

### Electrical Characteristics (@ $T_J = 25^\circ\text{C}$ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Unit
<b>Off Characteristics</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu A$	600	-	-	V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS} = 600V, V_{GS} = 0V, T_J = 25^\circ\text{C}$	-	-	1	$\mu A$
		$V_{DS} = 600V, V_{GS} = 0V, T_J = 150^\circ\text{C}$	-	-	50	$\mu A$
$I_{GSS}$	Gate-Body Leakage Current	$V_{GS} = \pm 30V, V_{DS} = 0V$	-	-	$\pm 100$	nA
<b>On Characteristics</b> *3						
$R_{DS(ON)}$	Static Drain-Source On-resistance	$V_{GS} = 10V, I_D = 7.5A$	-	-	0.24	$\Omega$
$V_{GS(th)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}, I_D = 250\mu A$	2.5	-	4.5	V
$R_G$	Gate Resistance	f=1.0MHz open drain	-	12.5	-	$\Omega$
<b>Dynamic Characteristics</b>						
$C_{ISS}$	Input Capacitance	$V_{GS} = 0V$	-	1306	-	pF
$C_{OSS}$	Output Capacitance	$V_{DS} = 100V$	-	62	-	
$C_{RSS}$	Reverse Transfer Capacitance	f = 1.0MHz	-	7	-	
<b>Switching Characteristics</b>						
$t_{d(ON)}$	Turn-on Delay Time	$V_{DS} = 400V$ $R_G = 25\Omega$ $I_D = 15A$	-	23	-	ns
$t_r$	Turn-on Rise Time		-	65	-	
$t_{d(OFF)}$	Turn-Off Delay Time		-	105	-	
$t_f$	Turn-Off Fall Time		-	50	-	
$Q_G$	Total Gate-Charge	$V_{DS} = 480V$	-	27	-	nC
$Q_{GS}$	Gate to Source Charge	$V_{GS} = 10V$	-	5.5	-	
$Q_{GD}$	Gate to Drain (Miller) Charge	$I_D = 15A$	-	10.5	-	
<b>Source-Drain Diode Characteristics</b>						
$V_{SD}$	Diode Forward Voltage	$I_S = 7A, V_{GS} = 0V$	-	-	1.2	V
$I_S$	Diode Continuous Forward Current	$T_C = 25^\circ\text{C}$	-	-	15	A
$I_{SM}$	Pulsed Source-Drain Current		-	-	45	A
$t_{rr}$	Reverse Recovery Time	$I_S = 15A, V_R = 400V$ $di_F/dt = 100A/\mu s$	-	410	-	ns
$Q_{rr}$	Reverse Recovery Charge		-	4.1	-	$\mu C$
$I_{rm}$	Peak Reverse Recovery Current		-	20	-	A

Notes:

1. Repetitive Rating: Pulse width limited by maximum junction temperature
2.  $I_{AS} = 2.4A, V_{DD} = 50V, R_G = 25\Omega, \text{Starting } T_J = 25^\circ\text{C}$
3. Pulse Test: Pulse width  $\leq 300\mu s, \text{Duty Cycle} \leq 1\%$

Ratings and Characteristics Curves (@  $T_J = 25^\circ\text{C}$  unless otherwise specified)




Fig 1 On-Region Characteristics




Fig 2 On-Resistance vs. Drain Current and Gate Voltage




Fig 3 Breakdown Voltage vs. Junction Temperature




Fig 4 Body-Diode Characteristics




Fig 5 Capacitance Characteristics




Fig 6 Transfer Characteristics




Fig 7 On-Resistance vs. Junction Temperature





Fig 8 Gate-Charge Characteristics

**Package Outline Dimensions** (Unit: mm)



**IMPORTANT NOTICE**

Changzhou Galaxy Century Microelectronics (GME) reserves the right to make changes without further notice to any product information (copyrighted) herein to make corrections, modifications, improvements, or other changes. GME does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others.